

# CAR & EQUIPMENT HAULERS

Whether you're hauling your vintage roadster to the weekend car show or moving equipment and supplies to a construction site, our car and equipment trailers meet the demand. Available in various lengths and axle sizes, these trailers are built to last for our Canadian climate and working conditions.



### EXPRESS

GREAT VALUE, QUALITY COMPONENTS & WORKMANSHIP

#### STANDARD FEATURES

- > 2" painted spruce floor
- > Easy lube spring axles
- > 4-leaf double eye suspension
- > 7,000 lb. GVWR Tandem 3,500 lb. axles
- > Metal preparation by sandblasting
- > 2-part epoxy primer
- > High quality black topcoat paint
- > Heavy duty stake pockets
- > Straight deck with 40" slide-in ramps (12' 14')
- > Straight deck with 5' slide-in ramps (16' and longer only)
- > Wiring enclosed in poly conduit
- > Sealed lights DOT rated
- > DOT Compliant safety chains
- > Removable straight fender with liner

#### **AVAILABLE OPTIONS**

- $\square$  9,900 lb. GVWR Tandem 5,200 lb. axles
- ☐ 14,000 lb. GVWR Tandem 7,000 lb. axles
- □ 2 5/16" height-adjustable coupler
- ☐ Height-adjustable pintle ring
- $\Box$  4' Lawn & garden ramp with 3,500 lb. rating (7,000 lb. GVWR trailer)
- □ 2' dovetail with 5' slide-in ramps (16' and longer only)
- ☐ Straight deck with sliding flip-up ramp
- □ 2' dovetail with sliding flip-up ramp
- ☐ Rear loading stands (standard on trailers 18' and longer)
- □ LED Lights upgrade
- □ Upgrade to 12K jack (14,000 lb. GVWR trailer)
- □ Spare tire □ Spare tire holder
- □ Rub rail □ D-rings

## Excursion

PREMIUM COMPONENTS & QUALITY WORKMANSHIP

#### STANDARD FEATURES

INCLUDES ALL EXPRESS STANDARD FEATURES, PLUS:

- > Stoneguard protection
- > Silver graphics package
- > LED Lights
- > Removable tear drop fender with liner
- > 12K Jack (14,000 lb. GVWR trailer)

#### **AVAILABLE OPTIONS**

ALL EXPRESS OPTIONS ARE AVAILABLE ON EXCURSION.

- $\hfill\Box$  Torflex axle upgrade
- ☐ Upgrade to G-range 14-ply tires (14,000 lb. GVWR trailer)
- ☐ Aluminum wheel upgrade
- ☐ Upgrade to diamond plate fenders
- ☐ Upgrade to 7K jack (7,000 lb. GVWR trailer)
- □ Upgrade to 12K jack (9,900 lb. GVWR trailer)



## CAR & EQUIPMENT HAULER STEEL SPECIFICATIONS



Ball Size   2 5/16"   2 2,40 lbs.   N/A   1.16   2 2,40 lbs.   N/A   1.16   2 2,500 lbs.   2,240 lbs.   1,16   1.16   2,500 lbs.   2,500 lbs.   2,500 lbs.   3,166 lbs.   1,16   1,16   1,16   2,100 lbs.   3,166 lbs.   1,16   1,16   2,100 lbs.   1,16   <	EXPRESS							
STATE   STAT		6312E	6314E	6316E	6318E	6320E		
G312M   G314M   G316M   G316M   G320M   G520M   G516M   G516M   G520M   G520M   T716M   T716M   T716M   T720M   T722M   T722				6516E	6518E	6520E		
G312M   G314M   G316M   G318M   G320M   G518M   G520M   T7718M   T7718M   T772M   T7				7716E	7718E	7720E	7722E	
Overall Length   16'   18'   20'   22'   24'   26'   22'   24'   26'   22'   24'   26'   22'   24'   26'   22'   24'   26'   22'   24'   26'   22'   24'   26'   22'   102"   22'   22'   22'   25'16"   25'16"   25'16"   25'16"   25'16"   25'16"   25'16"   25'16"   25'16"   25'16"   25'16"   25'16"   25'16"   25'16"	EXCURSION		ı					
Overall Length   16'   18'   20'   22'   24'   26'     Deck Length   12'   14'   16'   18'   20'   22'   24'   26'     Overall Width   102"   22"   102"   22"   16"   25/16"   25/16"   25/16"   25/16"   25/16" <td></td> <td>6312M</td> <td>6314M</td> <td></td> <td></td> <td></td> <td></td>		6312M	6314M					
Overall Length   16'   18'   20'   22'   24'   26'     Deck Length   12'   14'   16'   18'   20'   22'     Overall Width   102"   22"   22"   22"   22"   22"   22"   22"   22"   22"   25/16"   25/16"   25/16"   25/16"   25/16"   25/16"   25/16" <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>								
Deck Length   12'   14'   16'   18'   20'   22'     Overall Width   102"   100   100   100   100   100   100   100   100   100   100   100   100   100   100   100 <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>								
Overall Width   102"   22"   22"   6"   22"   6"   22"   6"   22"   6"   22"   6"   25/16"								
Between Fenders	· ·							
Hitch Weight (Estimated Empty)   175 lbs.   175 lbs.   175 lbs.   25/16"	Overall Width				102"			
Ball Size   2 5/16"		82"	82"	82"	82"	82"	82"	
Curb Weight 7K GVW   1,625 lbs.   1,700 lbs.   1,750 lbs.   1,800 lbs.   2,200 lbs.   N/A     Curb Weight 9.9K GVW   N/A   N/A   1,980 lbs.   2,115 lbs.   2,240 lbs.   N/A     Curb Weight 14K GVW   N/A   N/A   2,500 lbs.   2,644 lbs.   2,800 lbs.   3,166 lbs.     Payload Capacity 7K GVW   6,075 lbs.   6,000 lbs.   5,950 lbs.   5,900 lbs.   5,500 lbs.   N/A     Payload Capacity 9.9K GVW   N/A   N/A   8,910 lbs.   8,775 lbs.   8,650 lbs.   N/A     Payload Capacity 14K GVW   N/A   N/A   12,900 lbs.   12,756 lbs.   12,600 lbs.   12,234 lbs.     Brakes   Both Axles   Average of the Axles   Both Axles   Both Axles	Hitch Weight (Estimated Empty)	175 lbs.	175 lbs.	175 lbs.	300 lbs.	300 lbs.	300 lbs.	
Curb Weight 9.9K GVW   N/A   N/A   1.980 lbs.   2.115 lbs.   2.240 lbs.   N/A     Curb Weight 14K GVW   N/A   N/A   2.500 lbs.   2.644 lbs.   2.800 lbs.   3.166 lbs.     Payload Capacity 7K GVW   6.075 lbs.   6.000 lbs.   5.950 lbs.   5.900 lbs.   5.500 lbs.   N/A     Payload Capacity 9.9K GVW   N/A   N/A   8.910 lbs.   8.775 lbs.   8.650 lbs.   N/A     Payload Capacity 14K GVW   N/A   N/A   12.900 lbs.   12,756 lbs.   12,600 lbs.   12,234 lbs.     Brakes   Both Axles   Polug   RV Plug	Ball Size	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"	
Curb Weight 14K GVW   N/A   N/A   2,500 lbs.   2,644 lbs.   2,800 lbs.   3,166 lbs.     Payload Capacity 7K GVW   6,075 lbs.   6,000 lbs.   5,950 lbs.   5,900 lbs.   5,500 lbs.   N/A     Payload Capacity 9,9K GVW   N/A   N/A   8,910 lbs.   8,775 lbs.   8,650 lbs.   N/A     Payload Capacity 14K GVW   N/A   N/A   12,900 lbs.   12,756 lbs.   12,600 lbs.   12,234 lbs.     Brakes   Both Axles	Curb Weight 7K GVW	1,625 lbs.	1,700 lbs.	1,750 lbs.	1,800 lbs.	2,200 lbs.	N/A	
Payload Capacity 7K GVW   6,075 lbs.   6,000 lbs.   5,950 lbs.   5,900 lbs.   5,500 lbs.   N/A     Payload Capacity 9.9K GVW   N/A   N/A   8,910 lbs.   8,775 lbs.   8,650 lbs.   N/A     Payload Capacity 14K GVW   N/A   N/A   12,900 lbs.   12,756 lbs.   12,600 lbs.   12,234 lbs.     Brakes   Both Axles   Both A	Curb Weight 9.9K GVW	N/A	N/A	1,980 lbs.	2,115 lbs.	2,240 lbs.	N/A	
Payload Capacity 9.9K GVW   N/A   N/A   8,910 lbs.   8,775 lbs.   8,650 lbs.   N/A     Payload Capacity 14K GVW   N/A   N/A   12,900 lbs.   12,756 lbs.   12,600 lbs.   12,234 lbs.     Brakes   Both Axles   Both Axles   Both Axles   Both Axles   Both Axles     Electrical Hook-up   RV Plug   R	Curb Weight 14K GVW	N/A	N/A	2,500 lbs.	2,644 lbs.	2,800 lbs.	3,166 lbs.	
Payload Capacity 14K GVW   N/A   N/A   12,900 lbs.   12,756 lbs.   12,600 lbs.   12,234 lbs.     Brakes   Both Axles   Both Axles   Both Axles   Both Axles   Both Axles     Electrical Hook-up   RV Plug   Plug   SP TUG   RV Plug   RV Plug   RV Plug	Payload Capacity 7K GVW	6,075 lbs.	6,000 lbs.	5,950 lbs.	5,900 lbs.	5,500 lbs.	N/A	
Brakes   Both Axles   RV Plug   Plu	Payload Capacity 9.9K GVW	N/A	N/A	8,910 lbs.	8,775 lbs.	8,650 lbs.	N/A	
Electrical Hook-up   RV Plug   RV Plug <td>Payload Capacity 14K GVW</td> <td>N/A</td> <td>N/A</td> <td>12,900 lbs.</td> <td>12,756 lbs.</td> <td>12,600 lbs.</td> <td>12,234 lbs.</td>	Payload Capacity 14K GVW	N/A	N/A	12,900 lbs.	12,756 lbs.	12,600 lbs.	12,234 lbs.	
Slide in Ramps   10" x 40"   10" x 40"   12" x 60"   2" Spruce	Brakes	Both Axles	Both Axles	Both Axles	Both Axles	Both Axles	Both Axles	
Floor   2" Spruce   2"	Electrical Hook-up	RV Plug	RV Plug	RV Plug	RV Plug	RV Plug	RV Plug	
Gross Vehicle Weight   7000 GVW   9,900 GVW   14,000 GVW     Axles   2-3,500 lb.   2-5,200 lb.   2-7,000 lb.     Bolt Pattern   5-45 Bolt   8-65 Bolt   8-65 Bolt     Tires   15" C Range   15" D Range   16" E Range     Ply   6 Ply   8 Ply   10 Ply     Deck Length   12' - 20'   16' - 20'   16' - 22'     Deck Height   21"   22"   26"     Hitch Height   18"   19"   22"     Frame & Hitch   5" Channel   6" Channel   6" Channel (22' = 8" frame)     Crossmember   3" Channel   3" Channel   3" Channel     Crossmember Spacing   24"   24"   16"	Slide in Ramps	10" x 40"	10" x 40"	12" x 60"	12" x 60"	12" x 60"	12" x 60"	
Axles 2-3,500 lb. 2-5,200 lb. 2-7,000 lb.   Bolt Pattern 5-45 Bolt 6-55 Bolt 8-65 Bolt   Tires 15" C Range 15" D Range 16" E Range   Ply 6 Ply 8 Ply 10 Ply   Deck Length 12' - 20' 16' - 20' 16' - 22'   Deck Height 21" 22" 26"   Hitch Height 18" 19" 22"   Frame & Hitch 5" Channel 6" Channel 6" Channel (22' = 8" frame)   Crossmember 3" Channel 3" Channel 3" Channel   Crossmember Spacing 24" 24" 16"	Floor	2" Spruce	2" Spruce	2" Spruce	2" Spruce	2" Spruce	2" Spruce	
Bolt Pattern   5-45 Bolt   6-55 Bolt   8-65 Bolt     Tires   15" C Range   15" D Range   16" E Range     Ply   6 Ply   8 Ply   10 Ply     Deck Length   12' - 20'   16' - 20'   16' - 22'     Deck Height   21"   22"   26"     Hitch Height   18"   19"   22"     Frame & Hitch   5" Channel   6" Channel   6" Channel (22' = 8" frame)     Crossmember   3" Channel   3" Channel   3" Channel     Crossmember Spacing   24"   24"   16"	Gross Vehicle Weight	7000 GVW		9,900 GVW		14,000 GVW		
Tires 15" C Range 15" D Range 16" E Range   Ply 6 Ply 8 Ply 10 Ply   Deck Length 12' - 20' 16' - 20' 16' - 22'   Deck Height 21" 22" 26"   Hitch Height 18" 19" 22"   Frame & Hitch 5" Channel 6" Channel 6" Channel (22' = 8" frame)   Crossmember 3" Channel 3" Channel 3" Channel   Crossmember Spacing 24" 24" 16"	Axles	2-3,500 lb.		2-5,200 lb.		2-7,000 lb.		
Ply   6 Ply   8 Ply   10 Ply     Deck Length   12' - 20'   16' - 20'   16' - 22'     Deck Height   21"   22"   26"     Hitch Height   18"   19"   22"     Frame & Hitch   5" Channel   6" Channel   6" Channel (22' = 8" frame)     Crossmember   3" Channel   3" Channel   3" Channel     Crossmember Spacing   24"   24"   16"	Bolt Pattern	5-45 Bolt		6-55 Bolt		8-65 Bolt		
Deck Length   12' - 20'   16' - 20'   16' - 22'     Deck Height   21"   22"   26"     Hitch Height   18"   19"   22"     Frame & Hitch   5" Channel   6" Channel   6" Channel (22' = 8" frame)     Crossmember   3" Channel   3" Channel   3" Channel     Crossmember Spacing   24"   24"   16"	Tires	15" C Range		15" D Range		16" E Range		
Deck Height   21"   22"   26"     Hitch Height   18"   19"   22"     Frame & Hitch   5" Channel   6" Channel   6" Channel (22' = 8" frame)     Crossmember   3" Channel   3" Channel   3" Channel     Crossmember Spacing   24"   24"   16"	Ply	6 Ply		8 Ply		10 Ply		
Hitch Height   18"   19"   22"     Frame & Hitch   5" Channel   6" Channel   6" Channel (22' = 8" frame)     Crossmember   3" Channel   3" Channel   3" Channel     Crossmember Spacing   24"   24"   16"	Deck Length	12' - 20'		16' - 20'		16' - 22'		
Frame & Hitch   5" Channel   6" Channel   6" Channel (22' = 8" frame)     Crossmember   3" Channel   3" Channel   3" Channel     Crossmember Spacing   24"   24"   16"	Deck Height	21"		22"		26"		
Crossmember 3" Channel 3" Channel 3" Channel Crossmember Spacing 24" 24" 16"	Hitch Height	18"		19"		22"		
Crossmember Spacing 24" 24" 16"	Frame & Hitch	5" Channel		6" Channel		6" Channel (22' = 8" frame)		
	Crossmember	3" Ch	annel	3" Channel		3" Channel		
Jack   2,000 lb. A-Frame or Swivel   7,000 lb. Drop Leg   7,000 or 12,000 lb. Drop Leg	Crossmember Spacing	24"		24"		16"		
	Jack	2,000 lb. A-F	rame or Swivel	7,000 lb. Drop Leg		7,000 or 12,000 lb. Drop Leg		

Measurements are approximate and subject to change.

#### **RAINBOW TRAILERS** ARE THE BEST CHOICE FOR:

- > EASIER AND STRAIGHTER PULLING
- > DURABILITY AND LONGEVITY
- > SAFETY AND SECURITY

#### PLUS WE OFFER A 100% CANADIAN WARRANTY



#### RAINBOW TRAILERS

335 Broadway Street, Box 189 | Cartwright, MB, Canada ROK 0L0 P (204) 529 2581 | F (204) 529 2583 | E info@rainbowtrailers.net

CONTACT YOUR LOCAL RAINBOW TRAILER DEALER FOR MORE INFORMATION