

# CARGO TRAILERS 5'/6'/7' WIDE STEEL

A Rainbow Trailers Cargo Trailer is built with quality and designed to help you get your cargo or equipment from point A to point B in an environment protected from dust and weather.



## EXPRESS

### STANDARD FEATURES

- › 3/8" Plywood interior wall
- › Ramp transition flap
- › Easy lube spring axle
- › 4 Leaf spring suspension
- › Metal preparation by acid washing
- › 2 Part epoxy primer
- › High quality black topcoat paint
- › 0.030 Aluminum skin (black, white or pewter)
- › 3M VHB Taped exterior sidewalls (screwless)
- › Aluminum checker plate stone guard protection
- › Galvanized roof
- › Jeep style single aluminum fenders (teardrop on all tandem axle models)
- › Aerodynamic V-nose
- › 32" RV Style side door (6' & 7' wide)
- › Rear barn doors with lockable cam lock
- › All exterior wiring enclosed in poly conduit
- › DOT Compliant safety chains
- › DOT Compliant electric breakaway kit on all 5,000 lb. GVW trailers
- › DOT Compliant lights

### AVAILABLE OPTIONS - ALL

- Spare tire
- Spare tire holder
- Rear ramp door
- Extra height (6" increments)
- HD Scissor jacks
- E-track tie down system
- Interior light
- LED Lights
- Jack foot
- Bar lock on RV side door
- 3 1/2" Round wall vents
- Exterior loading lights
- Recessed floor mounted D-rings

## Excursion

### STANDARD FEATURES

INCLUDES ALL EXPRESS STANDARD FEATURES, PLUS:

- › One piece translucent roof
- › LED Lights
- › Jack foot
- › One 3 1/2" round wall vent
- › Hitch spray-on stoneguard
- › Primed steel under deck
- › Wall mounted interior light w/ switch

### AVAILABLE OPTIONS

ALL EXPRESS OPTIONS ARE AVAILABLE ON EXCURSION

- Torflex axle upgrade
- Aluminum wheel upgrade
- Aluminum wall vent
- 2 5/16" Height adjustable coupler
- Height adjustable pintle ring
- Upgrade to 7K jack (7,000 lb. GVWR)
- Motorcycle wheel chalk
- Extended V-Nose with front ramp door
- Beavertail
- Roof rack
- Dome light with switch
- Quad flooring
- Two tone colour
- Upgrade to 5,200 lb. axles (7' wide only)

## SUMMIT

### STANDARD FEATURES

INCLUDES ALL EXCURSION STANDARD FEATURES, PLUS:

- › 3/8" Luaun with white vinyl finish
- › E-track tie down system
- › Easy lube torflex axles
- › Dome light with switch
- › 16" o/c wall uprights & roof bows
- › Chrome centre caps
- › Ramp transition flap
- › Roof vent (adds 4" to overall height)

### AVAILABLE OPTIONS

ALL EXCURSION OPTIONS ARE AVAILABLE ON SUMMIT

- Insulation package

*\*Photos may contain options not included in the base trailer.*



| STEEL 1 x 3,500       | C5X8A13           | C5X10A13          | C6X10A13                 | C6X12A13                 | C6X14A13                 |
|-----------------------|-------------------|-------------------|--------------------------|--------------------------|--------------------------|
| Overall Length        | 11' 6"            | 13' 6"            | 14'                      | 16'                      | 18'                      |
| Overall Height        | 77.5" *           | 77.5" *           | 90"                      | 90"                      | 90"                      |
| Overall Width         | 81"               | 81"               | 93"                      | 93"                      | 93"                      |
| Interior Height       | 60" *             | 60" *             | 72"                      | 72"                      | 72"                      |
| Interior Length       | 8' + V-nose       | 10' + V-nose      | 10' + V-nose             | 12' + V-nose             | 14' + V-nose             |
| Interior Width        | 57"               | 57"               | 69"                      | 69"                      | 69"                      |
| Deck Height           | 16"               | 16"               | 16"                      | 16"                      | 16"                      |
| Hitch Height          | 11"               | 11"               | 13" to 14"               | 13" to 14"               | 13" to 14"               |
| Rear Opening - Height | 54.5" (Barn) *    | 54.5" (Barn) *    | 66.5" (Barn) 68" (Ramp)  | 66.5" (Barn) 68" (Ramp)  | 66.5" (Barn) 68" (Ramp)  |
| Rear Opening - Width  | 50" (Barn)        | 50" (Barn)        | 62" (Barn) 63.75" (Ramp) | 62" (Barn) 63.75" (Ramp) | 62" (Barn) 63.75" (Ramp) |
| Side Opening - Height | N/A               | N/A               | 66.5"                    | 66.5"                    | 66.5"                    |
| Side Opening - Width  | N/A               | N/A               | 30"                      | 30"                      | 30"                      |
| Ball Size             | 2"                | 2"                | 2"                       | 2"                       | 2"                       |
| Axles                 | 1 x 3500 lb.      | 1 x 3500 lb.      | 1 x 3500 lb.             | 1 x 3500 lb.             | 1 x 3500 lb.             |
| GAWR                  | 3,500 lbs.        | 3,500 lbs.        | 3,500 lbs.               | 3,500 lbs.               | 3,500 lbs.               |
| GVWR                  | 2,990 lbs.        | 2,990 lbs.        | 2,990 lbs.               | 2,990 lbs.               | 2,990 lbs.               |
| Curb Weight           | 926 lbs.          | 1,014 lbs.        | 1,202 lbs.               | 1,312 lbs.               | 1,422 lbs.               |
| Payload Capacity      | 2,363 lbs.        | 2,275 lbs.        | 2,087 lbs.               | 1,977 lbs.               | 1,867 lbs.               |
| Brakes                | Option            | Option            | Option                   | Option                   | Option                   |
| Tires - Radial        | 205/75R15C        | 205/75R15C        | 205/75R15C               | 205/75R15C               | 205/75R15C               |
| Ply                   | 6 Ply             | 6 Ply             | 6 Ply                    | 6 Ply                    | 6 Ply                    |
| Bolt Pattern          | 5-45 Bolt         | 5-45 Bolt         | 5-45 Bolt                | 5-45 Bolt                | 5-45 Bolt                |
| Frame & Hitch         | 3" x 2" tube      | 3" x 2" tube      | 3" x 2" tube             | 3" x 2" tube             | 3" x 2" tube             |
| Crossmembers          | 2" x 2" angle     | 2" x 2" angle     | 2" x 2" angle            | 2" x 2" angle            | 2" x 2" angle            |
| Crossmembers spacing  | 24" o/c           | 24" o/c           | 24" o/c                  | 24" o/c                  | 24" o/c                  |
| Jack                  | 2,000 lb. A-Frame | 2,000 lb. A-Frame | 2,000 lb. A-Frame        | 2,000 lb. A-Frame        | 2,000 lb. A-Frame        |
| Electrical Hook-up    | 7 Prong RV Plug   | 7 Prong RV Plug   | 7 Prong RV Plug          | 7 Prong RV Plug          | 7 Prong RV Plug          |
| Floor                 | 3/4" Plywood      | 3/4" Plywood      | 3/4" Plywood             | 3/4" Plywood             | 3/4" Plywood             |

| STEEL 2 x 3,500       | C6X10A23                    | C6X12A23                    | C6X14A23                    | C7X12A23                       | C7X14A23                       | C7X16A23                       | C7X18A23                       |
|-----------------------|-----------------------------|-----------------------------|-----------------------------|--------------------------------|--------------------------------|--------------------------------|--------------------------------|
| Overall Length        | 14'                         | 16'                         | 18'                         | 16' 6"                         | 18' 6"                         | 20' 6"                         | 22' 6"                         |
| Overall Height        | 91"                         | 91"                         | 91"                         | 91" *                          | 91" *                          | 91" *                          | 91" *                          |
| Overall Width         | 93"                         | 93"                         | 93"                         | 102"                           | 102"                           | 102"                           | 102"                           |
| Interior Height       | 72"                         | 72"                         | 72"                         | 72" *                          | 72" *                          | 72" *                          | 72" *                          |
| Interior Length       | 10' + V-nose                | 12' + V-nose                | 14' + V-nose                | 12' + V-nose                   | 14' + V-nose                   | 16' + V-nose                   | 18' + V-nose                   |
| Interior Width        | 69"                         | 69"                         | 69"                         | 78"                            | 78"                            | 78"                            | 78"                            |
| Deck Height           | 17"                         | 17"                         | 17"                         | 17"                            | 17"                            | 17"                            | 17"                            |
| Hitch Height          | 13" to 14"                  | 13" to 14"                  | 13" to 14"                  | 14" to 15"                     | 14" to 15"                     | 14" to 15"                     | 14" to 15"                     |
| Rear Opening - Height | 66.5" (Barn)<br>68" (Ramp)  | 66.5" (Barn)<br>68" (Ramp)  | 66.5" (Barn)<br>68" (Ramp)  | 66.5" (Barn)<br>68" (Ramp)*    | 66.5" (Barn)<br>68" (Ramp)*    | 66.5" (Barn)<br>68" (Ramp)*    | 66.5" (Barn)<br>68" (Ramp)*    |
| Rear Opening - Width  | 62" (Barn)<br>63.75" (Ramp) | 62" (Barn)<br>63.75" (Ramp) | 62" (Barn)<br>63.75" (Ramp) | 71.25" (Barn)<br>72.75" (Ramp) | 71.25" (Barn)<br>72.75" (Ramp) | 71.25" (Barn)<br>72.75" (Ramp) | 71.25" (Barn)<br>72.75" (Ramp) |
| Side Opening - Height | N/A                         | 66.5"                       | 66.5"                       | 66.5"                          | 66.5"                          | 66.5"                          | 66.5"                          |
| Side Opening - Width  | N/A                         | 30"                         | 30"                         | 30"                            | 30"                            | 30"                            | 30"                            |
| Ball Size             | 2 5/16"                     | 2 5/16"                     | 2 5/16"                     | 2 5/16"                        | 2 5/16"                        | 2 5/16"                        | 2 5/16"                        |
| Axles                 | 2 x 3,500 lb.               | 2 x 3,500 lb.               | 2 x 3,500 lb.               | 2 x 3,500 lb.                  | 2 x 3,500 lb.                  | 2 x 3,500 lb.                  | 2 x 3,500 lb.                  |
| GAWR                  | 7,000 lbs.                  | 7,000 lbs.                  | 7,000 lbs.                  | 7,000 lbs.                     | 7,000 lbs.                     | 7,000 lbs.                     | 7,000 lbs.                     |
| GVWR                  | 7,000 lbs.                  | 7,000 lbs.                  | 7,000 lbs.                  | 7,000 lbs.                     | 7,000 lbs.                     | 7,000 lbs.                     | 7,000 lbs.                     |
| Curb Weight           | 1,400 lbs.                  | 1,532 lbs.                  | 1,676 lbs.                  | 1,731 lbs.                     | 1,874 lbs.                     | 2,017 lbs.                     | 2,138 lbs.                     |
| Payload Capacity      | 6,300 lbs.                  | 6,168 lbs.                  | 6,024 lbs.                  | 5,969 lbs.                     | 5,826 lbs.                     | 5,683 lbs.                     | 5,562 lbs.                     |
| Brakes                | Standard                    | Standard                    | Standard                    | Standard                       | Standard                       | Standard                       | Standard                       |
| Tires - Radial        | 205/75R15C                  | 205/75R15C                  | 205/75R15C                  | 205/75R15C                     | 205/75R15C                     | 205/75R15C                     | 205/75R15C                     |
| Ply                   | 6 Ply                       | 6 Ply                       | 6 Ply                       | 6 Ply                          | 6 Ply                          | 6 Ply                          | 6 Ply                          |
| Bolt Pattern          | 5-45 Bolt                   | 5-45 Bolt                   | 5-45 Bolt                   | 5-45 Bolt                      | 5-45 Bolt                      | 5-45 Bolt                      | 5-45 Bolt                      |
| Frame & Hitch         | 4" x 2" tube                | 4" x 2" tube                | 4" x 2" tube                | Hitch 5" x 2" tube**           | Hitch 5" x 2" tube**           | Hitch 5" x 2" tube**           | Hitch 5" x 2" tube**           |
| Crossmembers          | 3" x 1 1/2" tube            | 3" x 1 1/2" tube            | 3" x 1 1/2" tube            | 3" x 1 1/2" tube               | 3" x 1 1/2" tube               | 3" x 1 1/2" tube               | 3" x 1 1/2" tube               |
| Crossmembers spacing  | 24" o/c                     | 24" o/c                     | 24" o/c                     | 24" o/c                        | 24" o/c                        | 24" o/c                        | 24" o/c                        |
| Jack                  | 2,000 lb. A-Frame           | 2,000 lb. A-Frame           | 2,000 lb. A-Frame           | 2,000 lb. A-Frame              | 2,000 lb. A-Frame              | 2,000 lb. A-Frame              | 2,000 lb. A-Frame              |
| Electrical Hook-up    | 7 Prong RV Plug             | 7 Prong RV Plug             | 7 Prong RV Plug             | 7 Prong RV Plug                | 7 Prong RV Plug                | 7 Prong RV Plug                | 7 Prong RV Plug                |
| Floor                 | 3/4" Plywood                | 3/4" Plywood                | 3/4" Plywood                | 3/4" Plywood                   | 3/4" Plywood                   | 3/4" Plywood                   | 3/4" Plywood                   |

\*Summit Class - all 5' & 7' will have 6" higher heights. \*\*Frame is 4" x 2" tube.

Measurements are approximate and subject to change.

**RAINBOW TRAILERS ARE THE BEST CHOICE FOR:**

- > EASIER AND STRAIGHTER PULLING
- > DURABILITY AND LONGEVITY
- > SAFETY AND SECURITY

**PLUS WE OFFER A 100% CANADIAN WARRANTY**



**RAINBOW TRAILERS**

335 Broadway Street, Box 189 | Cartwright, MB, Canada R0K 0L0  
 P (204) 529 2581 | F (204) 529 2583 | E info@rainbowtrailers.net

CONTACT YOUR LOCAL RAINBOW TRAILER DEALER FOR MORE INFORMATION