**EXPRESS | EXCURSION** 



# MEDIUM DECK ABOVE TRAILERS

Our medium deck above trailers, featuring new 8" I-Beam models, are built tough and strong for the rough northern climate and working conditions. Whatever your business is and whatever you're hauling, getting securely from point A to B has never been easier.



GREAT VALUE, QUALITY COMPONENTS & WORKMANSHIP

#### STANDARD FEATURES

- > 2" Painted spruce floor
- > Easy lube spring axles
- > Radial tires
- > Metal preparation by sandblasting
- > 2-Part epoxy primer
- > High quality black topcoat paint
- > Heavy duty stake pockets
- > Wiring enclosed in poly conduit
- > Height adjustable coupler
- > Sealed Lights DOT rated
- > DOT Compliant safety chains

### **AVAILABLE OPTIONS**

- ☐ Spare tire
- ☐ Spare tire holder
- □ LED Lights
- □ Rub rail
- □ D-rings
- □ Upgrade to Gooseneck hitch
- □ Slide in ramps (15" x 96")
- $\hfill \hfill \hfill$  3' Dovetail w/ flip up ramps (Only available on 9,900 lb. GVWR trailers 18' & longer)
- □ 4' Dovetail w/ flip up ramps (Only available on 14,000 lb. GVWR trailers 20' & longer)
- □ Upgrade from 7,000 lb. to 8,000 lb. axles



### Excursion

PREMIUM COMPONENTS & QUALITY WORKMANSHIP

#### STANDARD FEATURES

INCLUDES ALL EXPRESS STANDARD FEATURES, PLUS:

- > Stoneguard protection
- > Silver graphics package
- > LED Lights

#### **AVAILABLE OPTIONS**

ALL EXPRESS OPTIONS ARE AVAILABLE ON EXCURSION, PLUS: □ Torflex axle

upgrade □ Aluminum wheel

upgrade

\*Photos may contain options not included in the base trailer.



## MEDIUM DECK ABOVE TRAILER SPECIFICATIONS



	0516	0518	0520	O16A27	O18A27	O20A27	O22A27	O24A27
Overall Length	20' 9"	22' 9"	24' 9"	18' 8"	20' 8"	24' 8"	26' 8"	28' 8"
Deck Length	16' 4"	18' 4"	20' 4"	16' 5"	18' 5"	20' 5"	22' 5"	24' 5"
Overall Width	102"	102"	102"	102"	102"	102"	102"	102"
Deck Width	97.5"	97.5"	97.5"	97.5"	97.5"	97.5"	97.5"	97.5"
Deck Height	31"	31"	31"	35"	35"	35"	35"	35"
Hitch Height	20"-28"	20"-28"	20"-28"	24"-32"	24"-32"	24"-32"	24"-32"	24"-32"
Ball Size	2 5/16" Height Adjustable							
Axles	2-5,200 lb.	2-5,200 lb.	2-5,200 lb.	2-7,000 lb	2-7,000 lb.	2-7,000 lb.	2-7,000 lb.	2-7,000 lb.
GAWR	10,400 lbs.	10,400 lbs.	10,400 lbs.	14,000 lbs.				
GVWR	9,900 lbs.	9,900 lbs.	9,900 lbs.	14,000 lbs.	14,000 lbs.	14,000 lbs.	14,000 lbs.	14,000 lbs.
Curb Weight	2,446 lbs.	2,601 lbs.	2,756 lbs.	2,887 lbs.	3,064 lbs.	3,241 lbs.	3,418 lbs.	3,595 lbs.
Payload Capacity	8,444 lbs.	8,289 lbs.	8,134 lbs.	12,513 lbs.	12,336 lbs.	12,159 lbs.	11,982 lbs.	11,805 lbs.
Brakes	Both Axles							
Tires	225/75R15D	225/75R15D	225/75R15D	235/80R16E	235/80R16E	235/80R16E	235/80R16E	235/80R16E
Ply	8	8	8	10	10	10	10	10
Bolt Pattern	6-5.5 Bolt	6-5.5 Bolt	6-5.5 Bolt	8-6.5 Bolt				
Frame & Hitch	6" Channel	6" Channel	6" Channel	8" I-Beam				
Crossmembers	3" Channel							
Crossmembers Spacing	24"	24"	24"	16"	16"	16"	16"	16"
Jack	7K Drop Leg	7K Drop Leg	7K Drop Leg	12K Drop Leg*				
Electrical Hook-up	RV Plug							
Floor	2" Spruce							

Measurements are approximate and subject to change. \*5K Drop Leg standard on Express.

#### **RAINBOW TRAILERS** ARE THE BEST CHOICE FOR:

- > EASIER AND STRAIGHTER PULLING
- > DURABILITY AND LONGEVITY
- > SAFETY AND SECURITY

#### PLUS WE OFFER A 100% CANADIAN WARRANTY



#### **RAINBOW TRAILERS**

335 Broadway Street, Box 189 | Cartwright, MB, Canada ROK 0L0 P (204) 529 2581 | F (204) 529 2583 | E info@rainbowtrailers.net

CONTACT YOUR LOCAL RAINBOW TRAILER DEALER FOR MORE INFORMATION