

TILTING TRAILERS

Our tilting trailers make loading a breeze by eliminating the need for a ramp. Whether you need a full or partial tilt model, this trailer is built for business. You can depend on getting the job done when you choose Rainbow Trailers.



Excursion

PREMIUM COMPONENTS & QUALITY WORKMANSHIP

PARTIAL TILTING TRAILER

STANDARD FEATURES

- › 2" painted spruce floor
- › 14,000 lb. GVWR – Tandem 7,000 lb. axles
- › 6" Channel frame & hitch
- › 3" Channel cross members
- › Metal preparation by sandblasting
- › 2-part epoxy primer
- › High quality black topcoat paint
- › Stoneguard protection
- › Silver graphics package
- › Front bump rail
- › Heavy duty stake pockets
- › LED Lights
- › 9" x 72" Teardrop fenders with liner
- › Dovetail
- › Wiring enclosed in poly conduit
- › Gravity tilt with hydraulic cylinder
- › DOT Compliant safety chains

AVAILABLE OPTIONS

- Spare tire
- Spare tire holder
- Aluminum wheel upgrade
- Height adjustable pintle ring
- Rub rail
- D-rings
- Upgrade to diamond plate fenders

FULL TILTING TRAILER

STANDARD FEATURES

- › 2" painted spruce floor
- › 7,000 lb. GVWR – Tandem 3,500 lb. axles
- › 4-leaf double eye suspensions
- › 3" channel cross members
- › Metal preparation by sandblasting
- › 2-part epoxy primer
- › High quality black topcoat paint
- › Stoneguard protection
- › Silver graphics package
- › Front bump rail
- › Heavy duty stake pockets
- › LED Lights
- › 9" x 72" Teardrop fenders with liner
- › Dovetail
- › Wiring enclosed in poly conduit
- › Hydraulic jack for raising & lowering deck
- › Safety chains DOT rated

AVAILABLE OPTIONS

- 9,900 lb. GVWR – Tandem 5,200 lb. axles
- 14,000 lb. GVWR – Tandem 7,000 lb. axles
- Torflex axle upgrade
- Spare tire
- Spare tire holder
- Aluminum wheel upgrade
- 2 5/16" Height-adjustable pintle ring
- 2 5/16" Height-adjustable ball coupler
- Upgrade to 12K jack (9,900 lb. & 14,000 lb. GVWR trailer)
- Rub rail
- D-rings
- Upgrade to diamond plate fenders

**Photos may contain options not included in the base trailer.*

TILT TRAILER - PARTIAL & FULL SPECIFICATIONS



EXCURSION	FULL TILT			PARTIAL TILT
7K GVWR	8318M	8320M		
9.9K GVWR	8518M	8520M	8522M	
14K GVWR		8720M	8722M	8P7T22M
Overall Length	23' 5"	25' 10"	27' 10"	27' 10"
Deck Length Inc/30" Dove	18' 7"	20' 7"	22' 7"	22' 7"
Overall Width	102"	102"	102"	102"
Between Fenders	81 1/2"	81 1/2"	81 1/2"	81 1/2"
Hitch Weight (Approx.)	300 lbs.	340 lbs.	465 lbs.	610 lbs.
Ball Size	2 5/16"	2 5/16"	2 5/16"	2 5/16" (H/A)
Curb Weight 7K GVW	2,050 lbs.	2,130 lbs.	N/A	N/A
Curb Weight 9.9K GVW	2,280 lbs.	2,360 lbs.	2,723 lbs.	N/A
Curb Weight 14K GVW	N/A	2,635 lbs.	2,998 lbs.	3,085 lbs.
Payload Capacity 7K GVW	5,650 lbs.	5,570 lbs.	N/A	N/A
Payload Capacity 9.9K GVW	8,610 lbs.	8,530 lbs.	8,167 lbs.	N/A
Payload Capacity 14K GVW	N/A	12,765 lbs.	12,402 lbs.	12,315 lbs.
Brakes	Both Axles	Both Axles	Both Axles	Both Axles
Electrical Hook-up	RV Plug	RV Plug	RV Plug	RV Plug
Floor	2" Spruce	2" Spruce	2" Spruce	2" Spruce

	7,000 GVW	9,900 GVW	14,000 GVW	Partial Tilt 14,000 GVW
Axles	2-3,500 lb.	2-5,200 lb.	2-7,000 lb.	2-7,000 lb.
Bolt Pattern	5-45 Bolt	6-55 Bolt	8-65 Bolt	8-65 Bolt
Tires	15" C Range	15" D Range	16" E Range	16" E Range
Ply	6 Ply	8 Ply	10 Ply	10 Ply
Available Deck Lengths	18' - 20'	18' - 22'	20' - 22'	18' Plus 4' Stat
Hitch Height (Approx.)	18' - 19'	18' - 22'	19' - 22'	22"
Deck Height Spring	22"	23"	26"	N/A
Deck Height Torflex	19"	20"	23"	23"
Frame & Hitch	6" Channel	6" Channel	6" Channel	6" Channel
Crossmember	3" Channel	3" Channel	3" Channel	3" Channel
Crossmember Spacing	24"	24"	16"	16"
Jack	7,000 lb. Drop Leg	7,000 lb. Drop Leg	7000 lb. Drop Leg	12,000 lb. Drop Leg

Measurements are approximate and subject to change.

RAINBOW TRAILERS ARE THE BEST CHOICE FOR:

- > EASIER AND STRAIGHTER PULLING
- > DURABILITY AND LONGEVITY
- > SAFETY AND SECURITY

PLUS WE OFFER A 100% CANADIAN WARRANTY



RAINBOW TRAILERS

335 Broadway Street, Box 189 | Cartwright, MB, Canada R0K 0L0
 P (204) 529 2581 | F (204) 529 2583 | E info@rainbowtrailers.net

CONTACT YOUR LOCAL RAINBOW TRAILER DEALER FOR MORE INFORMATION